

HC20



HC20

- SPECIFICATIONS
- DESCRIPTION

•

Model	WIDS72V-HC20	WIDS72A-HC20	WIDS70-HC20	WIDS65-HC20	WIDP80-HC20	WIDP8A-HC20	WIDP7A-HC20
Image Sensor	1/3"SONY				1/3" CMOS		1/4" CMOS
TV System	PAL/NTSC						
Horizontal Resolution	720TVL, 960H	720TVL, 960H	700TVL, 960H	650TVL	800TVL, 960H	800TVL	700TVL
CCD+ISP	ICX663+EFFIO-V	ICX811AK+EFFIO-A	ICX811AK+EFFIO-E	ICX639BK+NVP2090	PC1099K	V8330+FH8520	BF3005
Effective Pixels	PAL:976(H)x582(V) NTSC:976(H)x494(V)			PAL: 752(H)x582(V) NTSC:768(H) x494(V)	P/N:960(H)480(V)	P/N: 720(H)x576(V)	P/N: 728(H)x488(V)
Usable Illumination	0.001 Lux/F2.0		0.01 Lux/F2.0		0.1 Lux/F2.0		
Sync System	Internal						
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec						
S/N Ratio	≥52dB		≥50dB		≥48dB		≥45dB
Gamma Correction	0.45						
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec						
White Balance	Auto						
IR Status	Under 10 Lux By CDS						

IR Power On	CDS Auto Control		
Video Out	Composite Signal (1.0Vp-p, 75Ω)		
Operation Temperature	-10°C ~ +50°C RH95% Max		
Storage Temperature	-30°C ~ +60°C RH95% Max		
UTC	Yes		No
OSD	DEFOG,Real WDR,3DNR	DEPOG, WDR, 3DNR,SLR, Sense Up	DWDR,DNR No
IR LED	ϕ 5X24pcs,20M working distance		
Lens	3.6mm Board Lens		
Waterproof	NO		